



Multipurpose Offshore Support Vessel

GLOMAR // VIKING

Safety Standby Wind Support & Survey



GLOMAR

Het Nieuwe Diep 34 A3
1781 AD Den Helder The Netherlands
T // +31 (0)223-525030 F // +31 (0)223-683372
info@gm-ships.com // www.gm-ships.com



SPECIFICATIONS:

Fleet of offshore support vessels

GENERAL:

Class:	USB
Flag:	Panama
Built / Rebuilt:	1988 / 2007
Call sign:	HO3363
IMO:	8906389
MMSI:	352697000
Type:	NOGEPa class standby vessel 120 survivors

DIMENSIONS:

Length:	45.7 m
Breadth:	9.0 m
Draft:	4.6 m
Depth:	5.1 m
GT:	660
NT:	198

PERFORMANCE:

Bollard Pull:	19 ton
Max Speed:	12 knots
Cruise Speed:	10 knots

MACHINERY & PROPULSION:

Main Engines:	Deutz SBV12M628 2206 KW
Gearboxes:	Reintjes GmbH WAV3463
Propellers & shafts:	FPP 4 blades
Auxiliary engines:	Doosan PU 08611 213Kw & Deutz BF8M1015MC 380 Kw
Harbor generator:	Deutz BF4M1013E 85Kw
Azimuth Thruster:	Kalkman Sigma Daf XF510 330KW
Bowthruster:	Tunneltruster electrical driven
Rudders:	Semi balanced
Engine room fire protection:	FM-200
Bilge water separator:	DVZ 500HCV
Fuel oil separator:	RWO
Electrical installation:	220 V - 380V 50 HZ

DECK & RESCUE EQUIPMENT:

Fast Rescue Craft:	GJ 6.10 9 Persons
Davit:	Noreq, NPD-3500
Deck crane:	Atlas AK 3006.6 SWL 0,950 Ton 4.58 meter
Sea rescue:	basket for 4 pers
Anchor winch:	2000M Radicon
Anchor chain:	2 x 200 m

DECK & LOADING CAPACITIES:

Deck area:	60 m ²
Deck load:	2.5 mt / m ²
Fuel oil:	155 m ³
Fresh water:	30.0 m ³

NAVIGATIONAL:

Modern navigational aids onboard.
Vessel is equipped for GMDSS area A1/ A2

ACCOMMODATION:

Crew cabins:	8 cabins 12 berths
--------------	--------------------