



HOS THUNDERFOOT

200 Offshore Supply Vessel



DIMENSIONS AND REGULATORY INFORMATION

Length:	190 ft 0 in (57.9 m)	Beam:	54 ft 0 in (16.5 m)	Draft Max:	13 ft 6 in (4.11 m)
Gross:	1,318 GT	Net :	395 NT	Draft Min:	8 ft 0 in (2.44 m)
IMO:	9211937	O.N.:	XCAR5	Flag:	Mexico
Certifications:	Oceans-SOLAS				
Classifications:	Loadline, American Bureau of Shipping, +DPS-1, +A1, +AMS				

PERFORMANCE

Max Speed:	13.0 kts 150 gal/hr (568 l/hr)
Cruise Speed:	10.0 kts 70 gal/hr (265 l/hr)

PROPULSION, MACHINERY AND STEERING

Main Engines:	2 x Caterpillar 3516B	Total Horsepower:	4,000 hp
Propellers:	FPP, High-Efficiency, 5-Blade	Propeller Diameter:	96in (2,438mm)
Primary Generators:	3 x Caterpillar 3406B	Total Rating:	750 kW
Bow Thruster:	1 x Brunvoll CPP Tunnel	Total Horsepower:	600 hp
Stern Thruster:	1 x SMI FPP Tunnel	Total Horsepower:	250 hp
Rudder:	Independent Steering, Schilling Fishtail	Power Generation:	480V/60 Hz/3-Phase

CAPACITIES AND DELIVERY RATES

Deadweight:	1,678 LT (1,705 MT)	Deck Area:	104ft x 46ft (4,784ft²) 31.7m x 14.0m (444.4m²)
Deck Cargo:	1,000 LT (1,016 MT)	Deck Load Rating:	1,024 lbs/ft² (5 MT/m²)
Dry Bulk:	7,000 ft³ (198 m³)	System Pressure:	80 psi (5.5 bar)
Potable Water:	54,562 gal (207 m³)	Discharge Rate:	550 GPM (125 m³/hr)
Rig Fuel:	293,501 gal (1,111 m³)	Discharge Rate:	550 GPM (125 m³/hr)
Rig Water:	148,567 gal (562 m³)	Freezer Area:	400 ft³ (11 m³)
Cooler Area:	400 ft³ (11 m³)	Total Flow Rate:	1,250 gal/min (284 m³/hr)
Off-ship Firefighting Monitors:	1		

ELECTRONICS

AIS, Auto Pilot, C-Nav, CCTV Cameras, Depth Sounder, DGPS, Fanbeam, GMDSS "A3", Gyro Compass, Joystick Control, Loudhailer, Mag Compass, MAMS/VMS, Nautronix JSDP 5000, Navtex, Public Phone System w/ loudhailer, SARTs, Single Side Band, VHF Radio, VHF Radio (Handheld), Windbird, X-band Radar

ACCOMMODATIONS

6 air conditioned/heated staterooms certified for 13 person berthing.

Additional deck berthing for 12 person(s)

SPECIAL FEATURES

Crane:	2 x Hydra Pro 20 Ton Telescoping Boom	Watermaker Cap. :	3,000 USG/day
Fenders:	4 x Yokohama Fenders per Side	Personnel Transfer:	Swing Rope Station
Freezer/Chillers:	2 x 20ft Refrigerated ISO Containers	Dry Stores:	2 x 20ft ISO Containers
Tow Hook:	100 MT SWL		

NOTICE: The information contained herein is provided solely for the convenience of reference, and Hornbeck does not warrant the accuracy or completeness of the data, which may vary from the current condition of the vessel or equipment. Hornbeck accepts no liability for the content of this document or for the consequences of any actions taken on the basis of the information provided, unless that information is subsequently confirmed in writing by an authorized representative.